

CLAIMS

1. (Previously Presented) A cross beam assembly comprising:
an air bag expandable from a folded condition to an expanded condition;
a beam having a hollow interior, said beam defining an opening formed therein;
an inflator assembly including a source of pressurized gas for inflating said air bag, said inflator assembly disposed within the hollow interior of said beam, such that activation of said inflator assembly expels gas through said opening, wherein said inflator assembly is integrally formed in said beam such that a portion of said beam defines walls of said inflator assembly; and
a chute connected to said beam, said chute having a passageway in communication with said opening formed in said beam, said chute extending outwardly from said beam for directing expelled gas from said source of pressurized gas to said air bag upon actuation of said inflator assembly, wherein said air bag is disposed in said chute when in the folded condition.
2. (Original) The assembly of claim 1, wherein said beam has a generally constant cross-sectional area along substantially the entire length of the beam.
3. (Previously Presented) The assembly of claim 2, wherein said beam includes a strengthening member defining a sleeve which is disposed over said beam and attached thereto, said strengthening member attached to a portion of said beam adjacent to said inflator assembly.
4. (Previously Presented) The assembly of claim 1, wherein said beam includes a strengthening member defining a sleeve which is disposed over said beam and attached thereto, said strengthening member attached to a portion of said beam adjacent to said inflator for providing added strength to said beam.
- 5 - 8. (Canceled).

9. (Previously Presented) The assembly of claim 1, wherein said cross beam includes a pair of walls disposed in said hollow interior of said beam, and wherein said walls and said hollow interior of said beam define a chamber for housing said source of pressurized gas.

10. (Previously Presented) The assembly of claim 9, wherein one of said walls is attached to said beam by a crimp formed in said beam.

11. (Previously Presented) The assembly of claim 9, wherein one of said walls is attached to said beam by a weld.

12 - 13 (Canceled).

14. (Previously Presented) The assembly of claim 1, wherein said chute partially surrounds said beam.

15 - 16. (Canceled).

17. (Previously presented) The assembly of claim 1 further including a door for covering said air bag in a non-deployed state, said door movable to deployed position upon actuation of said inflator to inflate said air bag, wherein said door is attached to said chute.

18. (Original) The assembly of claim 17, wherein said door is integrally formed with said chute.

19. (Original) The assembly of claim 1, wherein said source of pressurized gas is a solid propellant.

20. (Canceled).

21. (Previously presented) A cross beam assembly comprising:
an air bag expandable from a folded condition to an expanded condition;
a beam having a hollow interior, said beam defining an opening formed therein;
an inflator assembly including a source of pressurized gas for inflating said air bag, said inflator assembly disposed within the hollow interior of said beam, such that activation of said inflator assembly expels gas through said opening, wherein said inflator assembly is integrally formed in said beam such that a portion of the beam defines walls of said inflator assembly containing the source of pressurized gas;
a chute connected to said beam, said chute having a passageway in communication with said opening formed in said beam, said chute extending outwardly from said beam for directing expelled gas from said source of pressurized gas to said air bag upon actuation of said inflator assembly, wherein said air bag is disposed in said chute when in its folded condition; and
a door for covering said air bag when in its folded condition in said chute, said door being integrally formed with said chute, said door being movable to a deployed position upon actuation of said inflator to inflate said air bag.

22 - 23. (Canceled).

24. (Previously Presented) The assembly of claim 21, wherein said beam includes a strengthening member defining a sleeve which is disposed over said beam and attached thereto, said strengthening member attached to a portion of said beam adjacent to said inflator assembly.

25 - 27. (Canceled).